



Model No.: KR-75 N3RA
 MAX INLET: 5000 PSI
 REGULATED OUTLET: 500-2000 PSI
 SPECIFIED FLOW: 75 GPM
 Cv Outlet: 9.4
 Cv Vent: 1.40
 SUPPLY PORT: 1" NPT
 REGULATED OUTLET: 1" NPT
 VENT PORT : 1/2" NPT
 OPERATOR: AIR DIAPHRAGM; 120 PSI AIR PILOT
 TEMPERATURE RATING: -30°F TO 180°F
 WEIGHT: 65 LBS

- MATERIAL:
- BODY: STAINLESS STEEL
 - FLANGES & OPERATORS: CARBON STEEL
 - INTERNAL: STAINLESS STEEL
 - O-RINGS: BUNA (NITRILE)
 - BACKUPS:TEFLON

PacSeal HYDRAULICS INC.

VALVES, ACCUMULATORS, CONTROLS

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PacSeal Hydraulics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PacSeal Hydraulics IS PROHIBITED.

TITLE Regulator, KR-75
 N3RA Air Diaphragm
 Operator

SIZE A	DWG. NO. 40-1728	REV 1
SCALE: 1:4	WEIGHT: 64	SHEET 1 OF 2